

TATRA 810 M

MODERNIZED VERSION OF A MEDIUM CLASS ALL-WHEEL-DRIVE (6x6) OFF-ROAD LOGISTIC TRUCK

CAB

• COE; hydraulically tiltable forward; number of sitting people 1+2; HVAC; driver seat fully adjustable; independent heating; floor and engine protection against the effects of anti-personnel mines and hand grenades; individual filtration device

ENGINE

 RENAULT/VOLVO DTI 8: EURO 3: water cooled: direct fuel injection; turbocharged; intercooler; electronically controlled

number of cylinders 6 in line 7,7 1 volume

206 kW (280 HP)/ 2,200 min-1 power 1050 Nm/1100-1600 min⁻¹ torque

TRANSMISSION + TRANSFERCASE

- ZF 6S 1000 TO, manual, PTO output;
- number of gears (forward/reverse) 6/1
- VG 750; two-stage; shifting while the vehicle is stationary; with a torque divider with a lock

FRONT AXLE

• steered; driven; rigid; portal with reduction in wheel hubs; with permanent drive; differential lock; suspended by coil springs; telescopic shock absorbers and a transverse torsion stabilizer

REAR AXLES

driven; rigid; portal with reductions in wheel hubs; differential locks on both axles; inter-axle differential lock; suspended by leaf springs in a rocker arrangement

STEERING SYSTEM

• LHD; adjustable steering column in two axes

BRAKES

disc brakes; EBS; load sensor; 4 independent circuits: service, emergency, parking and engine (exhaust)

WHEELS

tires 365/85 X-FORCE ZL 20-10.00 V rims number of wheels 6+1 (spare)

ELECTRIC EQUIPMENT

voltage

batteries

alternator

WEIGHTS

24V

2x 12V, 180Ah

28V/110A

• curb	9,000 kg
payload max.	5,000 kg
• GVW	14,000 kg
max. front axle load	5,500 kg
 max. rear axle load 	2x 4,500 kg
• trailer	12.000 kg

TACTICAL PARAMETERS

max. speed (w. speed limiter)	110 km/h
gradient	60 %
trench width	900 mm
vertical step	480 mm
■ fording	1,200 mm
■ range	600 km
range of temperatures	-32 to +49 °C

EQUIPMENT

- flatbed
- hydraulic winch
- trailer hitch
- tow bar
- front and rear recovery/ tow eyes according to NATO standards
- 320 I fuel tank
- CTIS
- black-out/convoy lighting
- fire extinguisher
- roof hatch with possibility of mounting a Minimi 7.62 mm machine gun
- front protective frame













